NSN 5930-01-135-5555

Lock Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-135-5555 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.884 inches **Overall Height:** 1.575 inches **Overall Width:** 1.575 inches **Body Diameter:** 1.575 inches **Bushing Length:** 0.522 inches **Body Length:** 0.972 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **End Application:** 4920-01-054-8585 **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 1.375 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive dc and 100.000 milliamperes inductive dc and 1.000 amperes resistive ac and 250.000 milliamperes inductive ac **Precious Material And Location:** Contacts silver **Thread Series Designator:** Uns **Terminal Type And Quantity:**

Shelf Life: N/a

6 tab, solder lug

NSN 5930-01-135-5555

Lock Switch - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0