

View Online at <https://aerobasegroup.com/nsn/5930-01-135-8175>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Bushing Length:

0.310 inches

Body Length:

0.800 inches

Body Width:

0.390 inches

Body Height:

0.720 inches

Actuator Style:

Round

Actuator Diameter:

0.220 inches

Actuator Height:

0.580 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

0.650 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

5820-01-113-3277

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thready Qty Per Inch (tpi):

40

Pile-up Contact Form Arrangement:

1c single position

Thread Size:

0.250 inches

Switch Release Force:

1.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

12.0 ounces

Actuator Movement:

Between 0.010 pretravel inches and 0.003 overtravel inches and 0.007 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0