

View Online at <https://aerobasegroup.com/nsn/5930-01-135-8175>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Bushing Length:**

0.310 inches

**Body Length:**

0.800 inches

**Body Width:**

0.390 inches

**Body Height:**

0.720 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.220 inches

**Actuator Height:**

0.580 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

0.650 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

5820-01-113-3277

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thready Qty Per Inch (tpi):**

40

**Pile-up Contact Form Arrangement:**

1c single position

**Thread Size:**

0.250 inches

**Switch Release Force:**

1.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

12.0 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.003 overtravel inches and 0.007 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0