NSN 5930-01-135-9722

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-135-9722

Internal deactuation point screw and internal actuation point screw

Hazardous Locations/environmental Protection:
General purpose-nema type 1
Overall Length:
3.500 inches
Overall Height:
5.250 inches
Overall Width:
2.563 inches
Body Height:
4.625 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Capillary Tube Length:
72.0 inches
Bulb Length:
3.750 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
2.875 inches
Longest Vertical Distance Between Mounting Centers:
5.500 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Flange and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
5.0 amperes inductive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+310.00/+490.00 actuation point degrees fahrenheit and +305.00/+485.00 deactuation point degrees fahrenheit
Contact Adjustment Type:

NSN 5930-01-135-9722

Thermostatic Switch - Page 2 of 2



Contact Voltage Rating In Volts: 600.0 ac at sea level first voltage Special Features: Supplied with stainless steel bulb and capillary tube Media For Which Designed: Gas or liquid Style Designator: Rectangular Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A048b0