

View Online at <https://aerobasegroup.com/nsn/5930-01-136-1301>

**Inside Diameter:**

0.250 inches single connection

**Overall Length:**

4.188 inches

**Overall Height:**

5.125 inches

**Overall Width:**

4.688 inches

**Body Height:**

3.281 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Mounting Facility Centers:**

2.500 inches

**End Application:**

Cplg sft flex

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

30.00 inches of vacuum

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

-30.00/-0.00 actuation point inches of vacuum and -30.00/-0.00 deactuation point inches of vacuum

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0