

View Online at <https://aerobasegroup.com/nsn/5930-01-136-5393>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.448 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.625 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

End Application:

5805-01-105-9990

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

8 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug and turret

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

Precious Material And Location:

Rotor contacts and terminals gold

Precious Material:

Gold

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0