

View Online at <https://aerobasegroup.com/nsn/5930-01-136-6546>

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Overall Length:

3.250 inches

Outside Diameter:

0.438 inches single connection

Body Length:

2.554 inches

Overall Diameter:

1.390 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.687 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Electrical box connector

Contact Action Stimulus:

Decrease

Proof Pressure:

75.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

3.50 actuation point pounds per square inch gage and 4.50 deactuation point pounds per square inch gage and 1.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A048b0