

View Online at <https://aerobasegroup.com/nsn/5930-01-136-7080>

Overall Length:

Any acceptable

Power Cable Length:

24.000 inches

Ac Voltage Rating:

50.0 volts

Dc Voltage Rating:

50.0 volts

Frequency Rating:

60.0 hertz

Overall Diameter:

1.250 inches

Actuation Method:

Buoyancy

Electrical Connection Type:

Cable

Internal Battery Accommodation:

Not included

Current Rating At Maximum Rated Voltage:

0.04 amperes resistive load

Voltage Rating At Maximum Rated Current:

50.0 volts

Float Quantity:

1 and 1 and 1

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Thread

Mounting Position:

Vertical

Maximum Current Rating:

0.2 amperes resistive load

Contact Arrangement:

Spdt, normally open or normally closed

Relay:

Not included

Float Effective Travel:

32.500 inches

Mounting Dimensions:

Mtd by one 1-1/4-11 1/2 npt

Tank Insertion Length:

35.000 inches

Phase:

Single

Special Features:

Float effective travel 28.000 in. And 5.625 in. As differentiated by float quantity, float effective travel, and special features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T109-d