

View Online at <https://aerobasegroup.com/nsn/5930-01-136-7080>

**Overall Length:**

Any acceptable

**Power Cable Length:**

24.000 inches

**Ac Voltage Rating:**

50.0 volts

**Dc Voltage Rating:**

50.0 volts

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

1.250 inches

**Actuation Method:**

Buoyancy

**Electrical Connection Type:**

Cable

**Internal Battery Accommodation:**

Not included

**Current Rating At Maximum Rated Voltage:**

0.04 amperes resistive load

**Voltage Rating At Maximum Rated Current:**

50.0 volts

**Float Quantity:**

1 and 1 and 1

**Operating Temperature Rating:**

Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:**

Thread

**Mounting Position:**

Vertical

**Maximum Current Rating:**

0.2 amperes resistive load

**Contact Arrangement:**

Spdt, normally open or normally closed

**Relay:**

Not included

**Float Effective Travel:**

32.500 inches

**Mounting Dimensions:**

Mtd by one 1-1/4-11 1/2 npt

**Tank Insertion Length:**

35.000 inches

**Phase:**

Single

**Special Features:**

Float effective travel 28.000 in. And 5.625 in. As differentiated by float quantity, float effective travel, and special features

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T109-d