

View Online at <https://aerobasegroup.com/nsn/5930-01-136-9644>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.375 inches

Body Length:

0.500 inches

Body Width:

0.450 inches

Body Height:

0.350 inches

Actuator Style:

Round

Actuator Diameter:

0.218 inches

Actuator Height:

0.629 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts and terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0