

View Online at <https://aerobasegroup.com/nsn/5930-01-137-0010>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

0.720 inches

Overall Height:

2.675 inches

Overall Width:

0.670 inches

Bushing Length:

0.500 inches

Body Length:

0.720 inches

Body Width:

0.670 inches

Body Height:

0.875 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.300 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Alr62airborne

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 2.500 amperes inductive dc and 2.400 amperes lamp dc and 3.000 amperes motor dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 1.500 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0