Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-137-5301

	ocations/environmental Protection:
Dustproof	
Overall Leng	yth:
6.250 inches	
Overall Heig	ht:
2.906 inches	
Overall Widt	h:
2.812 inches	
Unthreaded	Mounting Hole Diameter:
0.221 inches	single mounting facility
Individual S	ection Quantity:
5	
Knob Manuf	acturer Code:
82121	
Knob Manuf	acturer Part Number:
G	
Longest Hor	izontal Distance Between Mounting Centers:
2.000 inches	single mounting facility
Shortest Ho	rizontal Distance Between Mounting Centers:
1.000 inches	single mounting facility
Longest Ver	tical Distance Between Mounting Centers:
2.188 inches	single mounting facility
End Applica	tion:
Control pane	I
Switch Conf	act Basic Design:
Nonpile-up s	ymmetrical
Pole Quanti	y:
1 each section	n rear
Throw Quan	tity:
1 each section	n rear
Mounting M	ethod:
Unthreaded I	nole single mounting facility
Features Pro	ovided:
Actuator kno	0
Contact Vol	age Rating In Volts:
	t ac voltage rating at sea level
Mounting Fa	ncility Pattern:
	ngle single mounting facility
	ator Indexing Position Quantity:
2 single actu	ator
Terminal Ty	
Tab w/screw	

# NSN 5930-01-137-5301

Rotary Switch - Page 2 of 2



**Contact Switching Action:** 

Makes before breaks each section rear

## Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

### Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0