

View Online at <https://aerobasegroup.com/nsn/5930-01-137-5408>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

19.950 inches

Overall Height:

1.791 inches

Overall Width:

1.156 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

24

Longest Horizontal Distance Between Mounting Centers:

19.780 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

16 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 each section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 16 positions each section

Special Features:

Twelve spacers are provided

Color:

White each indicator marking

Precious Material And Location:

Contact and printed circuit board circuit surfaces gold and contacts silver

Precious Material:

Gold and silver

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0