

View Online at <https://aerobasegroup.com/nsn/5930-01-138-6107>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.656 inches

Overall Height:

2.500 inches

First Flat Length:

0.750 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

3

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Longest Horizontal Distance Between Mounting Centers:

1.641 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.641 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0