

View Online at <https://aerobasegroup.com/nsn/5930-01-138-9278>

Thread Class:

2b single mounting facility

Overall Length:

6.562 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

355.0 dc at sea level500.0 highest ac voltage rating at sea level125.0 lowest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

400.0 milliamperes resistive load dc at sea level5.0 amperes resistive load highest ac voltage rating at sea level20.0 amperes resistive load lowest ac voltage rating at sea level

Precious Material And Location:

Contacts and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0