

View Online at <https://aerobasegroup.com/nsn/5930-01-138-9280>

**Thread Class:**

2b single mounting facility

**Overall Length:**

6.040 inches

**Overall Height:**

2.910 inches

**Overall Width:**

2.810 inches

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.180 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate and spring return

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Precious Material And Location:**

Rotor and stator surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0