## NSN 5930-01-138-9664



Pressure Switch - Page 1 of 2	-
View Online at https://aerobasegroup.com/nsn/5930-01-138-9664	
Overall Length:	
5.188 inches	
Overall Height:	
5.188 inches	
Overall Width:	
2.875 inches	
Body Length:	
4.875 inches	
Body Height:	
2.500 inches	
Unthreaded Mounting Hole Diameter:	
0.281 inches	
Longest Horizontal Distance Between Mounting Centers:	
2.406 inches	
Shortest Horizontal Distance Between Mounting Centers:	
1.750 inches	
Longest Vertical Distance Between Mounting Centers:	
3.281 inches	
Pressure Switch Type:	
Differential	
Mounting Method:	
Procket and unthreaded hele	

Bracket and unthreaded hole

**Features Provided:** 

Electrical access port

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

216.00 pounds per square inch

**Thread Size:** 

0.250 inches single pressure connection

**Mounting Facility Pattern:** 

Isosceles triangle

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

**Contact Load Current Rating:** 

9.6 amperes inductive load fourth voltage

**Contact Adjustability:** 

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Type:** 

External deactuation point screw and external actuation point screw

## NSN 5930-01-138-9664

Pressure Switch - Page 2 of 2



## Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Pressure Connector Type: Inverted flare, threaded external single connection Media For Which Designed: Gas or liquid Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0