# NSN 5930-01-138-9664

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-138-9664

Overall Length:

5.188 inches

**Overall Height:** 

5.188 inches

**Overall Width:** 

2.875 inches

Body Length:

4.875 inches

**Body Height:** 

2.500 inches

**Unthreaded Mounting Hole Diameter:** 

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

1.750 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

## **Features Provided:**

Electrical access port

## **Contact Action Stimulus:**

Increase

**Proof Pressure:** 

216.00 pounds per square inch

### **Thread Size:**

0.250 inches single pressure connection

#### Mounting Facility Pattern:

Isosceles triangle

#### **Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

### **Terminal Type:**

Screw

## **Contact Load Current Rating:**

9.6 amperes inductive load fourth voltage

### **Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

## Contact Adjustment Type:

External deactuation point screw and external actuation point screw

# NSN 5930-01-138-9664

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 550.0 dc at sea level third voltage Pressure Connector Type:

Inverted flare, threaded external single connection

## Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

## **Thread Series Designator:**

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A048b0