

View Online at <https://aerobasegroup.com/nsn/5930-01-138-9680>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.710 inches

Overall Height:

1.548 inches

Overall Width:

0.512 inches

Bushing Length:

0.315 inches

Body Length:

0.701 inches

Body Width:

0.512 inches

Body Height:

0.591 inches

Actuator Style:

Rectangular

Actuator Height:

0.485 inches

Actuator Width:

0.200 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

4920-01-034-7789

Mounting Surface To Terminal End Distance:

0.748 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal and contact surfaces gold and contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0