

View Online at <https://aerobasegroup.com/nsn/5930-01-138-9680>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.710 inches

**Overall Height:**

1.548 inches

**Overall Width:**

0.512 inches

**Bushing Length:**

0.315 inches

**Body Length:**

0.701 inches

**Body Width:**

0.512 inches

**Body Height:**

0.591 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.485 inches

**Actuator Width:**

0.200 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

4920-01-034-7789

**Mounting Surface To Terminal End Distance:**

0.748 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes resistive ac

**Precious Material And Location:**

Terminal and contact surfaces gold and contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0