NSN 5930-01-138-9683

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-138-9683

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.620 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Leaf

Actuator Free Position Height:

0.740 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

20.0 grams

Switch Actuating Force:

50.0 grams

Actuator Movement:

Between 0.140 pretravel inches and 0.062 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-138-9683

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

