# NSN 5930-01-139-1451

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-139-1451

**Thread Class:** 

3a single pressure connection

**Overall Length:** 

2.920 inches

**Outside Diameter:** 

1.135 inches single connection

**Overall Height:** 

Between 1.090 inches and 1.150 inches

**Overall Width:** 

1.500 inches

Body Length:

2.370 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.200 inches and 0.224 inches

**Distance Between Mounting Facility Centers:** 

1.120 inches

**End Application:** 

A/f-18-dcn

**Pressure Switch Type:** 

Gage

**Operating Tempurature Rating:** 

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:** 

Base and unthreaded hole

**Features Provided:** 

Hermetically sealed case

Thready Qty Per Inch (tpi):

20 single pressure connection

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

270.00 pounds per square inch

Thread Size:

0.500 inches single pressure connection

**Mounting Facility Pattern:** 

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:** 

800.00 pounds per square inch

**Terminal Type:** 

Connector, receptacle

# NSN 5930-01-139-1451

Pressure Switch - Page 2 of 2



Contact Load Current Rating
-----------------------------

1.0 amperes resistive load single voltage

#### **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

## **Contact Stimulus Rating:**

17.50 actuation point pounds per square inch and 15.00 deactuation point pounds per square inch and 2.50 differential point pounds per square inch

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

#### **Pressure Connector Type:**

Flared, threaded external single connection

#### Media For Which Designed:

Gas or liquid

#### **Style Designator:**

Rectangular

#### **Test Data Document:**

81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unf single pressure connection

# **Specification Data:**

81349-mil-s-9395/39 government specification

Shelf Life:

N/a

Unit Of Measure:

--

## **Demilitarization:**

Yes - demil/mli

Fiig:

A048b0