## ~4 120 4 4 69



<b>NSN 5930-01-139-1469</b> Push Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-01-139-1469
Thread Class:
2a
Body Style:
Bushing mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
0.512 inches
Overall Width:
0.311 inches
Bushing Length:
0.335 inches
Body Length:
0.512 inches
Body Width:
0.311 inches
Body Height:
0.827 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
End Application:
5895-01-121-3736
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
6.000 amperes resistive dc and 6.000 amperes resistive ac
Precious Material And Location:
Contact and terminal silver
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab, solder lug

Shelf Life:

N/a

## NSN 5930-01-139-1469

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

