

View Online at <https://aerobasegroup.com/nsn/5930-01-139-1470>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

0.512 inches

**Overall Width:**

0.311 inches

**Bushing Length:**

0.335 inches

**Body Length:**

0.512 inches

**Body Width:**

0.311 inches

**Body Height:**

0.827 inches

**Maximum Voltage Rating In Volts:**

125.0 ac and 28.0 dc

**End Application:**

5895-01-121-3736

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

6.000 amperes resistive dc and 6.000 amperes resistive ac

**Precious Material And Location:**

Contact and terminal surfaces silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0