# NSN 5930-01-139-1470

Push Switch - Page 1 of 2





# Thread Class:

2a

Body Style:

Bushing mounted

# Hazardous Locations/environmental Protection:

Watertight

#### **Overall Length:**

0.512 inches

**Overall Width:** 

0.311 inches

#### Bushing Length:

0.335 inches

Body Length:

#### 0.512 inches

Body Width:

### 0.311 inches

Body Height:

0.827 inches

### Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

#### End Application:

5895-01-121-3736

#### Inclosure Type:

Fully enclosed

## Mounting Method:

Threaded bushing

# Thready Qty Per Inch (tpi):

40

#### Thread Size:

0.250 inches

# Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

6.000 amperes resistive dc and 6.000 amperes resistive ac

#### **Precious Material And Location:**

Contact and terminal surfaces silver

## **Thread Series Designator:**

Uns

# Terminal Type And Quantity:

3 tab, solder lug

# Shelf Life:

N/a

# NSN 5930-01-139-1470

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

