

View Online at <https://aerobasegroup.com/nsn/5930-01-139-1514>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant and shock resistant and vibration resistant

Overall Length:

0.480 inches

Overall Height:

1.830 inches

Overall Width:

1.610 inches

Distance Between Mounting Facility Centers:

1.385 inches single mounting facility

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+71.0 degrees celsius

Mounting Method:

Flange single mounting facility and threaded hole single mounting facility

Actuator Type:

Toggle single actuator

Features Provided:

Rfi shielding

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4 single section

Contact Arrangement Truth Table:

Bcd, separate common to not-true bits, 2 pole - 10 positions single section

Special Features:

Stops provided to limit switch to 5 positions

Color:

White single indicator marking

Precious Material And Location:

Rfi shielding surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular indicating

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0