

View Online at <https://aerobasegroup.com/nsn/5930-01-139-1516>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Overall Length:**

0.480 inches

**Overall Height:**

1.830 inches

**Overall Width:**

1.610 inches

**Distance Between Mounting Facility Centers:**

1.385 inches single mounting facility

**Individual Section Quantity:**

1

**Operating Temperature Range:**

-55.0/+71.0 degrees celsius

**Mounting Method:**

Flange single mounting facility and threaded hole single mounting facility

**Actuator Type:**

Toggle single actuator

**Features Provided:**

Rfi shielding

**Thready Qty Per Inch (tpi):**

56 single mounting facility

**Thread Size:**

0.086 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3 single section

**Contact Arrangement Truth Table:**

Bcd, separate common to not-true bits, 2 pole - 10 positions single section

**Special Features:**

Stops provided to limit switch to 4 positions

**Color:**

White single indicator marking

**Precious Material And Location:**

Rfi shielding surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular indicating

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0