

View Online at <https://aerobasegroup.com/nsn/5930-01-139-2911>

Thread Class:

2a single mounting facility

Thread Length:

0.321 inches single mounting facility

Overall Length:

2.677 inches

Overall Diameter:

1.185 inches

Nonturn Device Radius:

0.390 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Pile-up Contact Form Arrangement:

3 each switch single section in-line

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 highest dc voltage rating at sea level

Shaft Flat/slot Angular Location:

210.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0