## NSN 5930-01-139-3896

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-139-3896

Body Style: Panel mount Overall Length: 1.000 inches Overall Height: 3.281 inches Overall Width: 0.750 inches Body Length: 0.905 inches Body Width: 0.685 inches Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Width: 0.430 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage:
Overall Length: 1.000 inches Overall Height: 3.281 inches Overall Width: 0.750 inches Body Length: 0.905 inches Body Width: 0.655 inches Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
1,000 inches  Overall Height: 3,281 inches  Overall Width: 0,750 inches  Body Length: 0,905 inches  Body Width: 0,655 inches  Body Height: 3,093 inches  Actuator Length: 0,680 inches  Actuator Style: Rectangular  Actuator Height: 0,188 inches  Actuator Width: 0,430 inches  Actuator Color: White single actuator  Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Overall Height: 3.281 inches Overall Width: 0.750 inches Body Length: 0.905 inches Body Width: 0.655 inches Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
3.281 inches  Overall Width: 0.750 inches  Body Length: 0.905 inches  Body Width: 0.655 inches  Body Height: 3.093 inches  Actuator Length: 0.680 inches  Actuator Style: Rectangular  Actuator Height: 0.188 inches  Actuator Width: 0.430 inches  Actuator Width: 0.430 inches  Actuator Color:  White single actuator  Illuminated Actuator Color:  White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application:  R.F.Test set  Inclosure Type: Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Overall Width: 0.750 inches Body Length: 0.905 inches Body Width: 0.655 inches Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator White single actuator Re.F. Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
0.750 inches  Body Length: 0.905 inches  Body Width: 0.655 inches  Body Height: 3.093 inches  Actuator Length: 0.680 inches  Actuator Style: Rectangular  Actuator Height: 0.188 inches  Actuator Width: 0.430 inches  Actuator Width: 0.430 inches  Actuator Color:  White single actuator  Illuminated Actuator Color:  White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application:  R.F. Test set  Inclosure Type: Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Body Length: 0.905 inches Body Width: 0.655 inches Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
0.905 inches  Body Width: 0.655 inches  Body Height: 3.093 inches  Actuator Length: 0.680 inches  Actuator Style: Rectangular  Actuator Height: 0.188 inches  Actuator Width: 0.430 inches  Actuator Width: 0.430 inches  Actuator Color: White single actuator  Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Body Width:  0.655 inches Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
0.655 inches  Body Height: 3.093 inches  Actuator Length: 0.680 inches  Actuator Style: Rectangular  Actuator Height: 0.188 inches  Actuator Width: 0.430 inches  Actuator Color: White single actuator  Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Body Height: 3.093 inches Actuator Length: 0.680 inches Actuator Style: Rectangular Actuator Height: 0.188 inches Actuator Width: 0.430 inches Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
3.093 inches  Actuator Length: 0.680 inches  Actuator Style: Rectangular  Actuator Height: 0.188 inches  Actuator Width: 0.430 inches  Actuator Color: White single actuator  Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Actuator Length:  0.680 inches  Actuator Style: Rectangular  Actuator Height:  0.188 inches  Actuator Width:  0.430 inches  Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
O.680 inches  Actuator Style: Rectangular  Actuator Height: O.188 inches  Actuator Width: O.430 inches  Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rif shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Actuator Style: Rectangular  Actuator Height: 0.188 inches  Actuator Width: 0.430 inches  Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Rectangular  Actuator Height:  0.188 inches  Actuator Width:  0.430 inches  Actuator Color:  White single actuator  Illuminated Actuator Color:  White single actuator  Maximum Voltage Rating In Volts:  250.0 ac  End Application:  R.F.Test set  Inclosure Type:  Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit
Actuator Height:  0.188 inches  Actuator Width:  0.430 inches  Actuator Color:  White single actuator  Illuminated Actuator Color:  White single actuator  Maximum Voltage Rating In Volts:  250.0 ac  End Application:  R.F.Test set  Inclosure Type:  Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit
O.188 inches  Actuator Width:  O.430 inches  Actuator Color:  White single actuator  Illuminated Actuator Color:  White single actuator  Maximum Voltage Rating In Volts:  250.0 ac  End Application:  R.F.Test set  Inclosure Type:  Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit
Actuator Width:  0.430 inches  Actuator Color: White single actuator  Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
O.430 inches  Actuator Color: White single actuator  Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed  Features Provided: Rfi shielding  Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Actuator Color: White single actuator Illuminated Actuator Color: White single actuator Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
White single actuator  Illuminated Actuator Color:  White single actuator  Maximum Voltage Rating In Volts:  250.0 ac  End Application:  R.F.Test set Inclosure Type:  Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit
Illuminated Actuator Color: White single actuator  Maximum Voltage Rating In Volts: 250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
White single actuator  Maximum Voltage Rating In Volts: 250.0 ac  End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Maximum Voltage Rating In Volts:  250.0 ac End Application: R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
250.0 ac  End Application:  R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
End Application:  R.F.Test set Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
R.F.Test set  Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Inclosure Type: Fully enclosed Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Fully enclosed  Features Provided:  Rfi shielding  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit
Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
Rfi shielding  Nonpile-up Contact Arrangement:  4 pole, double throw, one position momentary single switch unit
Nonpile-up Contact Arrangement: 4 pole, double throw, one position momentary single switch unit
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
$3.000 \ \text{amperes}$ resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac
Terminal Type And Quantity:
Terminal Type And Quantity: 17 tab, solder lug

N/a

## NSN 5930-01-139-3896

Push Switch - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A053a0