## NSN 5930-01-139-5176

Rotary Switch - Page 1 of 2



39-5176

| View Online at https://aerobasegroup.com/nsn/5930-01-1 |
|--|
| Thread Class:  |
| 2a single mounting facility                            |
| Thread Length:   |
| 0.469 inches single mounting facility                  |
| Hazardous Locations/environmental Protection:          |
| Watertight   |
| Overall Length:  |
| 2.657 inches   |
| Shaft Diameter:  |
| 0.250 inches single actuator                           |
| Shaft Length:  |
| 1.657 inches single actuator                           |
| Overall Diameter:                                      |
| 2.000 inches   |
| Individual Section Quantity:                           |
| 1  |
| Knob Manufacturer Code:                                |
| 82121  |
| Switch Contact Basic Design:                           |
| Nonpile-up symmetrical                                 |
| Pole Quantity:   |
| 1 single section rear                                  |
| Throw Quantity:  |
| 3 single section rear                                  |
| Mounting Method:                                       |
| Threaded bushing w/panel seal single mounting facility |
| Features Provided:                                     |
| Actuator knob  |
| Thready Qty Per Inch (tpi):                            |
| 32 single mounting facility                            |
| Thread Size:   |
| 0.469 inches single mounting facility                  |
| Contact Voltage Rating In Volts:                       |
| 125.0 ac at sea level                                  |
| Switch Actuator Momentary Position:                    |
| Counterclockwise single actuator                       |
| Switch Actuator Indexing Position Quantity:            |
| 3 single actuator                                      |
| Shaft Type:  |
| Round single actuator                                  |
| Terminal Type:   |

Tab w/screw

## NSN 5930-01-139-5176

Rotary Switch - Page 2 of 2



| Contact Switching Action:                     |
|---|
| Breaks before makes single section rear       |
| <b>Switch Actuator Positioning Increment:</b> |
| 45.0 degrees single actuator                  |
| Switch Actuator Stop Device Type:             |
| Fixed stop single actuator                    |
| Contact Load Current Rating:                  |
| 5.0 amperes resistive load ac at sea level    |
| Special Features:                             |
| Round threaded hole shaft                     |
| Style Designator:                             |
| Tap, circular, bushing mount                  |
| Thread Series Designator:                     |
| Uns single mounting facility                  |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |
| Demilitarization:                             |

No Fiig: A052b0