NSN 5930-01-139-5444

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-139-5444

	nvironmental Protection:
Dustproof	
Overall Length:	
5.376 inches	
Overall Height:	
2.906 inches	
Overall Width:	
2.812 inches	
Unthreaded Mounting	lole Diameter:
0.221 inches single mot	nting facility
Individual Section Qua	ntity:
2	
Knob Manufacturer Co	le:
82121	
Knob Manufacturer Pa	t Number:
С	
Longest Horizontal Dis	ance Between Mounting Centers:
2.000 inches single mot	nting facility
Shortest Horizontal Dis	tance Between Mounting Centers:
1.000 inches single mot	nting facility
Longest Vertical Dista	ce Between Mounting Centers:
2.188 inches single mot	nting facility
End Application:	
Switchboard	
Switch Contact Basic I	esign:
Nonpile-up symmetrical	
Pole Quantity:	
1 each section rear	
Throw Quantity:	
3 each section rear	
Mounting Method:	
Unthreaded hole single	nounting facility
Features Provided:	
Actuator knob	
Contact Voltage Rating	In Volts:
600.0 highest ac voltage	rating at sea level
Mounting Facility Patte	m:
Isosceles triangle single	nounting facility
Switch Actuator Indexi	ng Position Quantity:
4 single actuator	
Terminal Type:	
Tab w/screw	

NSN 5930-01-139-5444

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0