NSN 5930-01-139-5449

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-139-5449

Panel mount Overall Length: 1.197 inches Overall Height: 1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator Maximum Voltage Rating In Volts:						
1.197 inches Overall Height: 1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Overall Height: 1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator						
Up position maintained and down position maintained Actuator Color: White single actuator						
Actuator Color: White single actuator						
White single actuator						
•						
Maximum Voltage Rating In Volts:						
250.0 ac						
End Application:						
Mwbp						
Inclosure Type:						
Fully enclosed						
Mounting Method:						
Panel						
Nonpile-up Contact Arrangement:						
Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit						
2 pole, single throw, both positions maintained single switch unit						
2 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:						
2 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 16.000 amperes resistive ac						

N/a

NSN 5930-01-139-5449 Toggle Switch - Page 2 of 2



		eas	

Demilitarization:

No

Fiig:

A053a0