NSN 5930-01-139-5449

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-139-5449

Panel mount Overall Length: 1.197 inches Overall Height: 1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator Maximum Voltage Rating In Volts:
1.197 inches Overall Height: 1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Overall Height: 1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
1.318 inches Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Overall Width: 1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
1.028 inches Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Body Length: 1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
1.070 inches Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Body Width: 0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
0.870 inches Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Body Height: 0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
0.563 inches Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Actuator Length: 0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
0.794 inches Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Actuator Style: Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Rectangular Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Actuator Height: 0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
0.287 inches Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Actuator Width: 0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
0.793 inches Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Actuator Position-action Relationship: Up position maintained and down position maintained Actuator Color: White single actuator
Up position maintained and down position maintained Actuator Color: White single actuator
Actuator Color: White single actuator
White single actuator
•
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
Mwbp
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 2 pole, single throw, both positions maintained single switch unit
2 pole, single throw, both positions maintained single switch unit
2 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:
2 pole, single throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 16.000 amperes resistive ac

N/a

NSN 5930-01-139-5449 Toggle Switch - Page 2 of 2



		eas	

Demilitarization:

No

Fiig:

A053a0