

View Online at <https://aerobasegroup.com/nsn/5930-01-139-5453>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.387 inches

Body Length:

0.515 inches

Body Width:

0.465 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.580 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Actuator Position-locking Relationship:

Left position locked in and right position locked in

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Tt-775/g

Mounting Surface To Terminal End Distance:

0.520 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0