

View Online at <https://aerobasegroup.com/nsn/5930-01-139-5453>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.387 inches

**Body Length:**

0.515 inches

**Body Width:**

0.465 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.580 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Actuator Position-locking Relationship:**

Left position locked in and right position locked in

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Tt-775/g

**Mounting Surface To Terminal End Distance:**

0.520 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0