

View Online at <https://aerobasegroup.com/nsn/5930-01-140-4344>

**Thread Class:**

2b 1st mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

8.000 inches

**Overall Width:**

4.375 inches

**First Flat Length:**

1.375 inches single actuator

**Flat Height:**

0.250 inches single actuator

**Shaft Diameter:**

0.375 inches single actuator

**Shaft Length:**

1.375 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.312 inches 2nd mounting facility

**Individual Section Quantity:**

9

**Knob Manufacturer Code:**

82121

**Longest Horizontal Distance Between Mounting Centers:**

3.812 inches 2nd mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.281 inches 1st mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Bracket 1st mounting facility and threaded hole 1st mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

20 1st mounting facility

**Thread Size:**

0.250 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks 9th section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Special Features:**

Item must comply with requirements of desc production standard no. L03160; for navy nuclear propulsion plant products only

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc 1st mounting facility

**Reference Number Differentiating Characteristics:**

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A052b0