## NSN 5930-01-140-4626

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-140-4626

Body Style:

Panel mounted

**Body Width:** 

0.735 inches

Body Height:

0.685 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.240 inches

Inclosure Type:

Uninclosed

**Mounting Method:** 

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, two positions momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

## **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

12 tab, solder lug

**Specification Data:** 

81349-mil-s-22885/86 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0