

View Online at <https://aerobasegroup.com/nsn/5930-01-140-9490>

Thread Class:

2a single mounting facility

Thread Length:

0.290 inches single mounting facility and 0.330 inches single mounting facility

Overall Length:

Between 1.520 inches and 1.620 inches

Overall Height:

Between 1.485 inches and 1.515 inches

Overall Width:

Between 0.985 inches and 1.015 inches

First Flat Length:

0.369 inches single actuator and 0.416 inches single actuator

Flat Height:

0.198 inches single actuator and 0.198 inches single actuator

Shaft Diameter:

0.246 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.440 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

180.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.5 amperes resistive load ac at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0