

View Online at <https://aerobasegroup.com/nsn/5930-01-140-9490>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.290 inches single mounting facility and 0.330 inches single mounting facility

**Overall Length:**

Between 1.520 inches and 1.620 inches

**Overall Height:**

Between 1.485 inches and 1.515 inches

**Overall Width:**

Between 0.985 inches and 1.015 inches

**First Flat Length:**

0.369 inches single actuator and 0.416 inches single actuator

**Flat Height:**

0.198 inches single actuator and 0.198 inches single actuator

**Shaft Diameter:**

0.246 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.440 inches single actuator

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

180.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.5 amperes resistive load ac at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A052b0