NSN 5930-01-141-4764

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style: Panel mount

Shock resistant

Overall Length:
1.210 inches

Overall Height:
3.898 inches

Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-01-141-4764

Between 0.950 inches and 0.970 inches
Body Length:
1.200 inches
Body Width:
Between 0.950 inches and 0.970 inches
Body Height:
3.688 inches
Case Material:
Metal
Actuator Length:
Between 1.020 inches and 1.050 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.720 inches and 0.750 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Yellow single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

NSN 5930-01-141-4764

Push Switch - Page 2 of 2

Fiig: A053a0



Special Features:
High shock resistance; positive indexing; full display lens
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
12 turret and 7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No