NSN 5930-01-141-5671

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-141-5671
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture proof and shock proof
Overall Length:
0.755 inches
Overall Height:
3.060 inches
Overall Width:
0.755 inches
Body Length:
0.755 inches
Body Width:
0.755 inches
Body Height:
2.250 inches
Case Material:
Metal
Actuator Length:
0.755 inches
Actuator Style:
Rectangular
Actuator Width:
0.755 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Pump single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel Factures Provided:
Features Provided:
Actuator seal Nonnilo un Contact Arrangement:
Nonpile-up Contact Arrangement: 4 pole double throw one position memortary single switch unit
4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:
5 000 amperes resistive do and 2 500 amperes industive do and

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

NSN 5930-01-141-5671Push Switch - Page 2 of 2



Precious Material And Location:
Contacts silver and contact surfaces gold
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
19 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0