NSN 5930-01-142-0396

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-142-0396

Contact Load Current Rating At Maximum Rated Voltage:

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.740 inches
Overall Height:
3.060 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
Yellow single actuator and red single actuator
Illuminated Actuator Color:
Yellow single actuator and red single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator yellow lower half of actuator red
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Closed-loop
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

NSN 5930-01-142-0396

Push Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold and contacts silver
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
17 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A053a0