## NSN 5930-01-142-0398

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-142-0398

**Contact Load Current Rating At Maximum Rated Voltage:** 

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.740 inches
Overall Height:
3.060 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
Red single actuator and green single actuator
Illuminated Actuator Color:
Red single actuator and green single actuator
Actuator Inscription:
Enter/inputs matched single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator red lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Closed-loop
Inclosure Type:
Fully enclosed
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

## NSN 5930-01-142-0398

Push Switch - Page 2 of 2

No Fiig: A053a0



## Extra Long Reference Number: 800-8-a1c1e4j14l2m1n (rg) 18enter/inputs matched Precious Material And Location: Contact surfaces gold and contacts silver Unable To Decode: Unable to decode and unable to decode Terminal Type And Quantity: 17 pin Reference Number Differentiating Characteristics: Elrn Shelf Life: N/a Unit Of Measure: -- Demilitarization: