

View Online at <https://aerobasegroup.com/nsn/5930-01-142-5045>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

5.125 inches

Overall Height:

4.688 inches

Overall Width:

4.188 inches

Body Length:

3.281 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.500 inches

End Application:

Ind lght

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

10000.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

3 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+200.00/+3000.00 actuation point pounds per square inch and +200.00/+3000.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0