## NSN 5930-01-142-7836

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-142-7836

| Overall Length:  |
|--|
| 3.520 inches   |
| Overall Height:  |
| 1.740 inches   |
| Overall Width:   |
| 2.120 inches   |
| Unthreaded Mounting Hole Diameter:   |
| 0.189 inches single mounting facility  |
| Individual Section Quantity:   |
| 1  |
| Knob Manufacturer Code:  |
| 27192  |
| Knob Manufacturer Part Number:   |
| 53-1160  |
| Knob Specificationial Markings:  |
| Man-auto   |
| Longest Horizontal Distance Between Mounting Centers:  |
| 1.620 inches single mounting facility  |
| Longest Vertical Distance Between Mounting Centers:  |
| 1.250 inches single mounting facility  |
| End Application:   |
| 2starter mtr; elevators, aircraft; I.P. Compressors, air compressors, high pressure; cvn 68 class reactor fill auxiliary system; ticonderoga |
| class cg (47); spruancde class dd (963); forrestal class cv; arleigh burke class ddg; nimitz class cvn                                       |
| Switch Contact Basic Design:   |
| Nonpile-up nonsymmetrical  |
| Mounting Method:   |
| Unthreaded hole single mounting facility   |
| Features Provided:   |
| Actuator knob  |
| Contact Voltage Rating In Volts:   |
| 440.0 highest ac voltage rating at sea level   |
| Mounting Facility Pattern:   |
| Four position rectangular single mounting facility   |
| Criticality Code Justification:  |
| Feat   |
| Terminal Type:   |
| Tab w/screw  |
| Contact Switching Action:  |
| Breaks before makes single section rear  |
| Contact Load Current Rating:   |
| 7.5 amperes resistive load highest ac voltage rating at sea level  |

Weapon system essential

**Special Features:** 

## NSN 5930-01-142-7836

Rotary Switch - Page 2 of 2



| Styl | е | Des | ign | ator | : |
|------|---|-----|-----|------|---|
|      |   |     |     |      |   |

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0