NSN 5930-01-142-8726

Rotary Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-142-8726

| Hazardous Locations/environmental Protection: |
|---|
| Dustproof |
| Overall Length: |
| 3.499 inches |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 81487 |
| Knob Manufacturer Part Number: |
| Ks-11b |
| End Application: |
| Master contro |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Features Provided: |
| Actuator knob and cam actuated |
| Contact Voltage Rating In Volts: |
| 600.0 highest dc voltage rating at sea level |
| Cam Actuated Switch Contact Arrangement: |
| 1 two circuit, double break/double make, both positions maintained each switch each section in-line |
| Switch Actuator Indexing Position Quantity: |
| 2 single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes each section in-line |
| Switch Actuator Positioning Increment: |
| 90.0 degrees single actuator |
| Contact Load Current Rating: |
| 6.0 amperes resistive load lowest ac voltage rating at sea level |
| Style Designator: |
| In-line, cam actuated |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |