

View Online at <https://aerobasegroup.com/nsn/5930-01-143-0165>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Body Diameter:**

1.015 inches

**Bushing Length:**

1.000 inches

**Body Length:**

0.980 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Free Position Height:**

0.375 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

0.070 pretravel inches and 0.010 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

**Special Features:**

Lead 1 cut to 7.500 in. Lg, lead 3 cut to 8.000 in. Lg, lead 4 cut to 9.000 in. Lg, lead 6 cut to 11.000 in. Lg; leads 2 and 5 cut to 4.000 in. Lg and tape

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0