NSN 5930-01-143-0933

Thermostatic Switch - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-143-0933

| 1.656 inches |
|--|
| Overall Height: |
| 2.875 inches |
| Overall Width: |
| 2.422 inches |
| Body Height: |
| 2.375 inches |
| Distance Between Mounting Facility Centers: |
| 1.812 inches |
| Capillary Tube Length: |
| Between 42.0 inches and 72.0 inches |
| Bulb Length: |
| 11.250 inches |
| Bulb Diameter: |
| 0.188 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Bracket and threaded hole |
| Thready Qty Per Inch (tpi): |
| 32 all threaded hole |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.138 inches all threaded hole |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Quick disconnect, male |
| Contact Load Current Rating: |
| 30.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |
| Contact Adjustment Range: |
| $+200.00/+550.00\ actuation\ point\ degrees\ fahrenheit\ and\ +200.00/+550.00\ deactuation\ point\ degrees\ fahrenheit\ and\ point\ point\ point\ point\ po$ |
| Contact Adjustment Type: |
| External deactuation point shaft with scale and external actuation point shaft with scale |
| Contact Voltage Rating In Volts: |
| 250.0 ac at sea level single voltage |

NSN 5930-01-143-0933

Thermostatic Switch - Page 2 of 2



| Media For Which Des | signed: |
|---------------------|---------|
|---------------------|---------|

Gas or liquid

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0