NSN 5930-01-143-3026

Thermostatic Switch - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-143-3026

5.188 inches		
Overall Width:		
2.812 inches		
Body Height:		
2.750 inches		
Unthreaded Mounting Hole Diameter:		
0.281 inches		
Capillary Tube Length:		
25.0 inches		
Bulb Length:		
3.000 inches		
Bulb Diameter:		
0.375 inches		
Longest Horizontal Distance Between Mounting Centers:		
2.406 inches		
Shortest Horizontal Distance Between Mounting Centers:		
0.656 inches		
Longest Vertical Distance Between Mounting Centers:		
3.281 inches		
End Application:		
Switch		
Tempurature Sensing Element Type:		
Capillary tube-bulb		
Mounting Method:		
Bracket and unthreaded hole		
Features Provided:		
Electrical access port		
Contact Action Stimulus:		
Increase		
Mounting Facility Pattern:		
Isosceles triangle		
Nonpile-up Contact Arrangement:		
1 pole, double throw, one position momentary		
Terminal Type:		
Screw		
Contact Load Current Rating:		
9.6 amperes inductive load fourth voltage		

Contact Adjustment Range:

Deactuation point adjustable and actuation point adjustable

Contact Adjustability:

+90.00/+215.00 actuation point degrees fahrenheit and +90.00/+215.00 deactuation point degrees fahrenheit

NSN 5930-01-143-3026

Thermostatic Switch - Page 2 of 2



Contact A	Adjustment	Type:
-----------	------------	-------

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A048b0