

View Online at <https://aerobasegroup.com/nsn/5930-01-143-4976>

Thread Class:

2a single mounting facility

Thread Length:

0.247 inches single mounting facility

Overall Length:

1.312 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.997 inches single actuator and 1.003 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

0.623 inches

Nonturn Device Radius:

0.250 inches at 12:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 12:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

2 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

8.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts rotor blades and terminal surfaces gold

Precious Material:

Gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0